

PTZ-3330-01

Outdoor - Pan Tilt Zoom - IP Camera

The PTZ-3330-01 is a high-resolution, low light, color video camera with an 18X motor driven optical zoom and a 4X digital multiplier providing 72X total zoom. The camera has outstanding performance in both daylight and low-light conditions, with low-light performance to 0.005 lux. The pan, tilt and zoom functions can be controlled automatically and precisely from anywhere through the IVC Relay Server.

The system packages an auto-focus camera, lens and heater in a small, weatherproof dome enclosure. Powder-coated aluminum construction makes the system ideal for outdoor applications.

The unit includes an IP module for local storage of pre- and post-event video, approximately 1000 frames of video at 320x240 resolution.



Specifications

Imager	¼ inch CCD	Tilt Angle	-90° to +5°
Shutter	1 to 1/10,000 Seconds	Ethernet	100Base-TX/10BaseT (RJ-45)
Exposure	Auto	I/O Terminals	4 inputs, 4 outputs
Min. Illumination	0.7 Lux (Color) 0.005 Lux (B/W)	Resolution	640x480, 320x240
White Balance	Auto	Compression	MPEG4, M-JPEG
Iris	Auto	Frame Rate	30 FPS (320x240) 30 FPS (640x480)
Gain	Auto and Manual	Protocols	TCP/IP, HTTP, FTP, SMTP
Focus	Auto	Weight	17 lbs
Zoom Ratio	18x Optical; 4x Multiplier	Power Req.	110VAC
View Angle	2.7° - 48°	Power Cons.	45W
Focal Length	4.1 - 73.8 mm	Operating Temp.	-20° to +122° Fahrenheit
F-number	1.4	Dimensions	14"H x 11"D (Camera Enclosure) 15"L x 5.5"H x 4"W (Mounting Arm)
Pan Angle	360°		
Pan Speed	170° per Second		