



SPEEDCHECK-12



- Calendar/schedule operation
- Data collection with visualization and reporting software
- Mobile app for iOS® and Android™
- Rapid-flashing strobe

- Stealth mode
- On-board diagnostic status and health indicators
- 3-year warranty

Fully Compliant, Ultra-clear Display

Compliant to MUTCD standards for legibility, including LED color, character and letter height. The bright LED display uses 12-inch digits against a background designed for high-contrast visibility that prevents "88" ghosting—ensuring readability in all weather and lighting conditions. The unique safety mask limits the viewing angle to prevent drivers from watching the display as they pass.

Long-lasting, Reliable Operation

The LED display is housed within a durable, weatherproof aluminum unit and is shielded with a tough polycarbonate window for added vandalism protection. Every solarpowered model is solar-sized by location to ensure yearafter-year operation. Carmanah includes a Solar Power Report to prove sustainability over a 12-month period.

Easy Installation and Connectivity

The SpeedCheck® sign arrives ready to work out of the box. Its modular, lightweight design and built-in handle allows a single person to install on a pole or flat surface. Bluetooth® allows for quick connectivity and setup via the SpeedCheck Manager mobile app or PC software. A StreetHub™ model comes factory prewired and pretested for remote communication—enabling cloud-based access within minutes. Carmanah's comprehensive support system includes product support technologists and our 24/7 on-demand Product Support Center.





Buy America compliant



3-year limited warranty



Solar-sized for every location




Up to 21 days battery run time



Up to 1000 feet radar detection

LED DISPLAY



LED Display and Strobe	Meets MUTCD legibility standards for character height and LED color for roadways with speed limits under 45 mph	
	Seven-segment digit design using 224 amber LEDs LEDs automatically dim during nighttime operation, minimizing light bounce into neighboring windows	
	Includes rapid-flashing strobe with white LEDs at the center of the display (with ON/OFF setting)	
	Includes stealth mode for data collection	
Radar	Detection range up to 800 ft; extended range option available	
	Single-direction, K Band Doppler radar (+/- 1 mph) with 12° radar beam width	
Construction	Weatherproof, gasketed enclosure with vents for ambient air transfer	
	Corrosion-resistant aluminum chassis with stainless steel hardware	
	3/16" polycarbonate window protects digital display from weather and vandalism	
	Keyed access prevents sign removal and battery theft	
Weight	15 lbs (6.8 kg) without batteries	

COMMUNICATION		
Local	Bluetooth mobile app and PC software (SpeedCheck Manager)	
Remote	Optional StreetHub model includes fully integrated monitoring un from the factory and Glance cloud-based software for two-way communication, reporting and monitoring	

POWER OPTIONS		
Battery	Up to 21 days battery run time (3,000 ADT)	
	Includes external battery charger	
	Maintenance-free, non-proprietary AGM batteries offer the widest	
	temperature range and longest life	
	Batteries can be easily replaced at low cost	
Solar	12 VDC operation, solar sized to specific geographic location	
	Includes 12-month Solar Power Report to ensure system sustainability	
	System designed for 5+ year battery life	
AC	100-240 VAC in standard configurations	

INCLUDED WITH EVERY SIGN		
Software and Mobile App	SpeedCheck Manager mobile app for quick changes to high-touch settings, via Bluetooth	
	SpeedCheck Manager PC software for all setup and programming options, including calendar scheduling, data collection, via Bluetooth	
	Traffic Analyzer software for data visualization and reporting	
Hardware and	High-powered Bluetooth dongle for up to 50 ft range between	
Installation	SpeedCheck sign and PC	
Setup	Radar installation kit with alignment tool and foam cone	
Warranty	3-year limited warranty on LED display	
	1-year limited warranty on batteries	
Support	Carmanah's North American product support technologists available	
	for solution building, solar sizing and troubleshooting	
	24/7 access to Carmanah's online Product Support Center database	

"YOUR SPEED" STATIC SIGN Sign Meets MUTCD legibility standards for color, character and height 3M High Intensity Prismatic or Diamond Grade retroreflective Sheeting sheeting and components Color Available in yellow, fluorescent yellow/green, white, and orange







24" x 22' (610 mm x 559 mm) *Not FHWA MUTCD compliant

30" x 24" (762 mm x 610 mm)

30" x 36" (762 mm x 914 mm)

Standard Banding/ Through Bolt (2" - 2.5" Flat Surface

Through Bolt (2.38" - 2.88" & 4.5" Diameter Square Poles) Round Poles)

Band Clamps (2.38" - 4.75" & 5.5 - 8.25" Diameter Round Poles)









SOLAR KITS AND MOUNTS

Top of Pole Mount







PANEL	LENGTH	WIDTH
30 W	21.5" (545 mm)	15.7" (400 mm)
50 W	26.3" (668 mm)	21.2" (538 mm)

LEARN MORE ABOUT THE PRODUCT

- What's a Solar Power Report?
- Visit the Product Support Center